





Brass Barb Fittings, Tubing, and Accessories







Selection Chart

Brass Barb Fittings, Tubing, and Accessories (Part 1 of 4)

Figure	Code Number	Description and Use												
	F-1000-320 F-1000-2	Tubing Clamps: Barrel Type For Flexible Tubing Tubing Size: 5/32 in. O.D. (100 pk) 1/4 in. O.D. (100 pk)												
	F-1000-3 F-1000-4 F-1000-5	Sealing Caps: Rubber (100 pks) For use with Copper and Plastic Tubing Tubing Size: 3/16 in. Tubing and Barbed Fittings for 1/4 in. Tubing 1/4 in. Tubing and Barbed Fittings for 3/8 in. Tubing 3/8 in. Tubing These are not for permanent installations; use only during construction.												
	F-1000-361	Sealing Cap with Test Point for 1/4 in. Barb Fitting (10 pk)												
	F-1000-231 F-1000-324 F-1000-355 F-1000-397	Blue Urethane Tubing: Max Temp 140°F Max Press 25 psig 1/4 in. O.D. x 1/8 in. I.D. 5/32 in. O.D. x 3/32 in. I.D. Code number represents 1 foot of tubing (order in multiples of 100 ft). 1/8 in. O.D. x 1/16 in. I.D. Code number represents 1 ft of tubing (order in multiples of 50 ft). 5/32 in. O.D. x 3/32 in. I.D. Code number represents 1 ft of tubing (order in multiples of 25 ft).												
	F-1000-153 F-1000-322 F-1000-395	Spring Inserts: Anti-Kink To insert inside: <table border="1"> <thead> <tr> <th>Tubing L.D. (in.)</th><th>Spring Length (in.)</th><th>Material</th></tr> </thead> <tbody> <tr> <td>1/8</td><td>10</td><td>Brass (50 pk)</td></tr> <tr> <td>3/32</td><td>8</td><td>S.S. (50 pk)</td></tr> <tr> <td>3/32</td><td>8</td><td>S.S. (10 pk)</td></tr> </tbody> </table>	Tubing L.D. (in.)	Spring Length (in.)	Material	1/8	10	Brass (50 pk)	3/32	8	S.S. (50 pk)	3/32	8	S.S. (10 pk)
Tubing L.D. (in.)	Spring Length (in.)	Material												
1/8	10	Brass (50 pk)												
3/32	8	S.S. (50 pk)												
3/32	8	S.S. (10 pk)												
	F-300-31 F-300-30 F-300-26 F-300-27 F-300-21 F-300-20 F-300-19 F-300-32 F-300-33 F-300-34 F-300-35 F-200-36	Couplings: Straight Barb x Barb Size (in.): 5/32 x 5/32 (100 pk) 1/4 x 5/32 (100 pk) 1/4 x 1/4 (100 pk) 3/8 x 3/8 (50 pk) 3/8 x 1/4 (50 pk) 1/2 x 1/4 (50 pk) 1/2 x 3/8 (50 pk) 3/8 x 1/4 (10 pk) 1/4 x 1/4 (10 pk) 1/4 x 5/32 (10 pk) 5/32 x 5/32 (10 pk) 1/2 x 1/2 (50 pk)												
	F-500-39 F-500-38 F-500-37 F-500-45 F-500-47	Couplings: Elbow Barb x Barb Size (in.): 1/4 x 1/4 (50 pk) 3/8 x 3/8 (100 pk) 1/2 x 1/2 (50 pk) 5/32 x 5/32 (Plastic, 50 pk) 1/4 x 1/4 (10 pk)												

Brass Barb Fittings, Tubing, and Accessories (Continued)






Brass Barb Fittings, Tubing, and Accessories (Part 2 of 4)

Figure	Code Number	Description and Use
	F-700-83 F-700-94 F-700-86 F-700-84 F-700-95 F-700-73 F-700-90 F-700-85 F-700-74 F-700-91 F-700-75 F-700-92 F-700-67 F-700-66 F-700-65	Couplings: Tee Barb x Barb x Barb Size (in.): 5/32 x 5/32 x 5/32 (Brass, 50 pk) 5/32 x 5/32 x 5/32 (Brass, 10 pk) 5/32 x 5/32 x 5/32 (Plastic, 100 pk) 1/4 x 1/4 x 5/32 (100 pk) 1/4 x 1/4 x 5/32 (10 pk) 1/4 x 1/4 x 1/4 (100 pk) 1/4 x 1/4 x 1/4 (10 pk) 3/8 x 3/8 x 5/32 (100 pk) 3/8 x 3/8 x 1/4 (50 pk) 3/8 x 3/8 x 1/4 (10 pk) 3/8 x 3/8 x 3/8 (50 pk) 3/8 x 3/8 x 3/8 (10 pk) 1/2 x 1/2 x 1/4 (50 pk) 1/2 x 1/2 x 3/8 (50 pk) 1/2 x 1/2 x 1/2 (50 pk)
	F-400-20	Coupling Fitting NPT x NPT Size (in.): 1/8 x 1/8 (25 pk)
	F-400-10	Adaptor Fitting Compression x NPT Size (in.): 1/4 x 1/8 (25 pk)
	F-100-21 F-100-22 F-200-35	Adaptors: Straight Male Barb x NPT Size (in.): 5/32 or 1/4 x 1/8 (100 pk) 5/32 x 1/4 x 1/8 (10 pk) 3/8 x 1/8 (50 pk)
	F-500-41 F-500-48 F-500-36	Adaptor Elbows: Male Barb x NPT Size (in.): 1/4 x 1/8 (100 pk) 1/4 x 1/8 (10 pk) 3/8 x 1/8 (100 pk)
	F-500-42	Adaptor Elbow: Female Barb x NPT Size (in.): 1/4 x 1/8 (50 pk)
	F-700-79	Adaptor Tee: Male Barb x Barb x NPT Size (in.): 1/4 x 1/4 x 1/8 (50 pk)
	F-700-80	Adaptor Tee: Female, Drop Eared Barb x Barb x NPT Size (in.): 1/4 x 1/4 x 1/8 (10 pk)

The performance specifications are nominal and conform to acceptable industry standards. For applications at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls, Inc. shall not be liable for damages resulting from misapplication or misuse of its products. © 2011 Johnson Controls, Inc. www.johnsoncontrols.com

Brass Barb Fittings, Tubing, and Accessories (Continued)

Brass Barb Fittings, Tubing, and Accessories (Part 3 of 4)

Figure	Code Number	Description and Use
	F-700-76 F-700-93	Adaptor Tee: Female Barb x Barb x NPT Size (in.): 1/4 x 1/4 x 1/8 (100 pk) 1/4 x 1/4 x 1/8 (10 pk)
	F-700-62	Adaptor Tee: Gauge Barb x NPT x NPT Size (in.): 1/4 x 1/8 x 1/8 (50 pk)
	F-200-33 F-200-40 F-200-37 F-200-41 F-200-38	Adaptors: Plastic to Copper/Aluminum Barb x Compression Size (in.): 1/4 x 1/4 (50 pk) 1/4 x 1/4 (10 pk) 3/8 x 3/8 (50 pk) 3/8 x 3/8 (10 pk) 1/2 x 1/2 (25 pk)
	F-100-20	Adaptor: Plastic to Copper Barb x Sweat Size (in.): 5/32 O.D. x 3/16 (100 pk)
	F-1000-323 F-1000-396 F-1000-241 F-1000-289	Plugs Size (in.): 1/4 or 5/32 (100 pk) 1/4 or 5/32 (10 pk) 3/8 (100 pk) 1/2 (50 pk)
	F-1000-198 F-1000-394 F-1000-184 F-1000-8	Inserts: Metal for Polyethylene Tubing (Color-Black) Tubing Size (in.): O.D.: 1/4 I.D.: 0.165 to 0.171 (100 pk) O.D.: 1/4 I.D.: 0.165 to 0.171 (10 pk) O.D.: 3/8 I.D.: 0.246 to 0.256 (100 pk) O.D.: 1/2 I.D.: 0.371 to 0.381 (100 pk) Use one metal insert (black) for each compression fitting connection to polyethylene tubing.
	F-1000-9 F-1000-10 F-1000-11	Ferrules: Plastic Tubing Size (in.): 1/4 (100 pk) 3/8 (100 pk) 1/2 (100 pk) Replace standard brass ferrule with this ferrule when using compression fittings for polyethylene tubing.
	T-800-6001 F-1000-13	Ferrules: For Copper Tubing Size (in.): 1/4 (100 pk) 3/8 (100 pk)
	F-700-7 F-700-87	Adaptor, Tee: Female Tube x Tube x NPT Size (in.): 1/4 x 1/4 x 1/8 (50 pk) 1/4 x 1/4 x 1/8 (10 pk)

Brass Barb Fittings, Tubing, and Accessories (Continued)

Brass Barb Fittings, Tubing, and Accessories (Part 4 of 4)

Figure	Code Number	Description and Use
	F-800-3 F-800-9 F-800-4 F-800-5 F-800-6 F-800-7	Couplings: Straight Tube x Tube Size (in.): 1/4 x 1/4 (100 pk) 1/4 x 1/4 (10 pk) 3/8 x 1/4 (50 pk) 3/8 x 3/8 (50 pk) 1/2 x 3/8 (25 pk) 1/2 x 1/2 (25 pk)
	F-500-18	Coupling: Elbow Tube x Tube Size (in.): 1/2 x 1/2 (25 pk)
	F-700-9 F-700-88 F-700-44 F-700-10 F-700-11 F-700-12 F-700-13	Couplings: Tee Tube x Tube x Tube Size (in.): 1/4 x 1/4 x 1/4 (50 pk) 1/4 x 1/4 x 1/4 (10 pk) 3/8 x 1/4 x 1/4 (25 pk) 3/8 x 3/8 x 1/4 (25 pk) 3/8 x 3/8 x 3/8 (25 pk) 1/2 x 1/2 x 3/8 (10 pk) 1/2 x 1/2 x 1/2 (10 pk)
	F-1000-14 F-1000-393	Sealing Cap: Compression 1/4 in. (50 pk) 1/4 in. (10 pk)
	F-1000-35	Nut: Compression 1/4 in. (100 pk)
	F-200-2 F-200-3 F-200-39 F-1000-36 F-200-4 F-200-5 F-200-6 F-200-8 F-200-9	Adaptors: Straight, Male Tube x NPT Size (in.): 3/16 x 1/8 (100 pk) 1/4 x 1/8 (100 pk) 1/4 x 1/8 (10 pk) 1/4 x 1/4 (100 pk) 3/8 x 1/8 (50 pk) 3/8 x 1/4 (50 pk) 3/8 x 3/8 (50 pk) 1/2 x 3/8 (25 pk) 1/2 x 1/2 (25 pk)
	F-500-2 F-500-3 F-500-46 F-500-4 F-500-5 F-500-6 F-500-8 F-500-9	Adaptors: Elbow, Male Tube x NPT Size (in.): 3/16 x 1/8 (50 pk) 1/4 x 1/8 (25 pk) 1/4 x 1/8 (10 pk) 3/8 x 1/8 (50 pk) 3/8 x 1/4 (25 pk) 3/8 x 3/8 (50 pk) 1/2 x 3/8 (25 pk) 1/2 x 1/2 (25 pk)