

M9108-JGx-2 Series 3-Wire Resistive Electric Non-spring Return Actuators

The M9108-JGx-2 Series direct-mount electric actuators operate on 24 VAC or VDC power, and are available for use with resistive input controllers. These bidirectional actuators do not require a damper linkage, and are easily installed on a damper with a round shaft up to 3/4 in. (19 mm) in diameter or a square shaft up to 5/8 in. (16 mm). They may be direct- or remote-mounted to a damper.

A single M9108-JGx-2 model delivers up to 70 lb·in (8 N·m) of torque. The angle of rotation is mechanically adjustable from 0 to 90° in 5-degree increments. Integral auxiliary switches are available to indicate end-stop position or to perform switching functions at any angle within the selected rotation range. A jumper on the actuator allows users to select the direction of action. Position feedback is available through a 0 to 10 VDC signal.



Figure 1: M9108 Series Actuator

Features and Benefits	
☐ Output Position Feedback	Provides simple, closed-loop control with accurate position sensing
☐ Electronic Stall Detection	Ensures higher reliability by deactivating the actuator motor if a stall condition is detected
☐ Dual Scale (0 to 90° and 90 to 0°) on the Cover	Indicates the position of the actuator's rotation in 10° increments
☐ Removable Coupler	Allows adjustment of the rotation range from 0 to 90°
☐ Steel U-bolt Clamp	Provides four-point damper shaft gripping
☐ Coupled to a Ball-style Valve with Linkage	Regulates the flow of hot or chilled water, 50% glycol solution, and low pressure steam
☐ Jumper-selectable Rotation Direction and Manual Gear Release	Simplifies installation, setup, and field adjustments
☐ Noise Filter	Eliminates repositioning due to line noise
☐ National Pipe Thread (NPT) Threaded Housing	Provides easy connection for electrical fittings

Application

IMPORTANT: This device is not designed or intended to be used in or near environments where explosive vapors or gases could be present, or environments where substances corrosive to the device's internal components could be present.

The M9108-JGx-2 actuators may be mounted in any convenient orientation. They are designed to position air dampers and valves in Heating, Ventilating, and Air Conditioning (HVAC) systems. Applications include:

- positioning return air or exhaust dampers
- controlling face and bypass dampers
- positioning blades for variable volume fans

Refer to the manufacturer's information to properly size the damper, valve, and/or actuator. Spring return actuators, such as Johnson Controls® M9206 and M9216 Series, are recommended for use with outdoor air dampers in cold climates.

Operation

IMPORTANT: The M9108-JGx-2 Series actuators are intended to control equipment under normal operating conditions. Where failure or malfunction of an M9108-JGx-2 actuator could lead to an abnormal operating condition that could cause personal injury or damage to the equipment or other property, other devices (limit or safety controls), or systems (alarm or supervisory) intended to warn of, or protect against, failure or malfunction of the M9108-JGx-2 actuator must be incorporated into and maintained as part of the control system.

M9108-JGx-2 actuators operate on 24 VAC at 50/60 Hz or 24 VDC. These compact actuators use a DC motor with stall detection circuitry that operates throughout the entire stroke. The M9108-JGx-2 actuator employs noise-filtering techniques on the control signal to eliminate repositioning due to line noise.

Rotation is mechanically limited to 93° by integral end-stops. The position of the actuator is marked from 0 to 90° on the cover. An anti-rotation bracket prevents lateral movement of the actuator. Press the spring-loaded gear release on the actuator cover to disengage the gear train for manual repositioning of the coupler.

Dimensions

See Figure 2 for actuator dimensions.




Figure 2: Actuator and Anti-Rotation Bracket Dimensions, in. (mm)

Ordering Information

Table 1: Actuator Models and Accessories

Product Code Number	Description
M9108-JGA-2	70 lb-in (8 N·m) electric non-spring return actuator with 3-wire resistive input control and 24 VAC/VDC input
M9108-JGC-2	70 lb-in (8 N·m) electric non-spring return actuator with 3-wire resistive input control and 24 VAC/VDC input and two SPDT 24 VAC auxiliary switches
DMPR-KR003*	Sleeve Pin Kit for Johnson Controls round dampers with a 5/16 in. (8 mm) diameter shaft
DMPR-KC003*	Blade Pin Extension without Bracket for Johnson Controls D-1300 direct-mount applications
DMPR-KC254	Inside Frame Mounting Kit for Johnson Controls dampers that require the actuator within the airstream
M9000-103	14 VA Transformer, 120/24 VAC, 60 Hz, Class 2
M9000-104	14 VA Transformer, 230/24 VAC, 60 Hz, Class 2
M9000-150	Damper Mount Linkage Kit for remote inside duct mounting an M9108 actuator to a three-blade or larger damper (not intended for a Johnson Controls damper)
M9000-151	Base Mount Linkage Kit for remote inside duct mounting
M9000-153	Crank Arm Kit for remote mounting
M9000-154	1 in. Jackshaft Coupler Kit for mounting on a 1 in. diameter damper shaft
M9000-155	Manual Handle for positioning a damper or valve when power is removed from an M9108 actuator
M9000-160	Replacement anti-rotation bracket for M9108 actuators
M9000-300	Weather Shield Enclosure protects M9108 actuators in outdoor damper applications

* Furnished with the damper and may be ordered separately.

Technical Specifications

Product	M9108-JGx-2 Series On/Off and Floating Electric Non-spring Return Actuators	
Power Requirements	20 to 30 VAC at 50/60 Hz or 24 VDC $\pm 10\%$; 7.5 VA supply, Class 2	
Input Signal	Potentiometer value is 100 ohms minimum to 10,000 ohms maximum	
Input Signal Adjustments	Action is jumper selectable Direct Clockwise (CW) or Reverse Counterclockwise (CCW) with signal increase.	
Input Impedance	1.8 megohms	
Feedback Signal	0 to 10 VDC for 90° (10 VDC at 1mA)	
Auxiliary Switch Rating	JGC:	Two Single-Pole, Double-Throw (SPDT) switches rated at 24 VAC 1.5 A inductive, 3.0 A resistive; 35 VA maximum per switch, Class 2
Mechanical Output (Running Torque)	70 lb·in (8 N·m) for one unit; not intended for tandem use	
Audible Noise Rating	45 dBA at 1 m	
Rotation Range	0 to 90° in 5-degree increments, mechanically limited to 93°	
Rotation Time	30 seconds at 50% rated load, 25 to 50 seconds for 0 to 70 lb·in (0 to 8 N·m)	
Electrical Connection	Screw terminals for 22 to 14 AWG; maximum of two 18, 20, or 22 AWG per terminal	
Mechanical Connection	3/8 to 3/4 in. (10 to 20 mm) diameter round shaft or 3/8 to 5/8 in. (10 to 16 mm) square shaft	
Enclosure	NEMA 2, IP42	
Ambient Conditions	Operating:	-4 to 122°F (-20 to 50°C); 0 to 95% RH, noncondensing
	Storage:	-40 to 186°F (-40 to 86°C); 0 to 95% RH, noncondensing
Dimensions (H x W x D)	7.09 x 3.94 x 2.54 in. (180 x 100 x 64.5 mm)	
Shipping Weight	2.9 lb (1.3 kg)	
Agency Compliance	UL Listed, File E27734, CCN XAPX CSA Certified, File LR85083, Class 3221 02 CE Mark, EMC Directive 89/336/EEC	



The performance specifications are nominal and conform to acceptable industry standards. For application at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls shall not be liable for damages resulting from misapplication or misuse of its products.



Johnson Controls
507 E. Michigan Street
P.O. Box 423
Milwaukee, WI 53201

Published in U.S.A.
www.johnsoncontrols.com